RS CORPORATION

Jyotitech Solar™
Energising Future

TECHNICAL DATA SHEET

JTS 165


165 Wp Monocrystalline Solar Module

165 Wp
MAXIMUM POWER

19.98 %
MODULE EFFICIENCY

1500 V DC
MAX. SYSTEM VOLTAGE

Class II
SAFETY CLASS



1080 × 765 × 30 mm · 9.5 kg · Illustrative image

Electrical Parameters

PARAMETER	SYMBOL	VALUE
Maximum Power	P_{max}	**165 Wp**
Maximum Power Tolerance		**± 3 %**
Maximum Power Voltage	V_{mp}	**18.51 V**
Maximum Power Current	I_{mp}	**8.92 A**
Open Circuit Voltage	V_{oc}	**22.48 V**
Short Circuit Current	I_{sc}	**9.48 A**
Maximum System Voltage		**1500 V DC**
Maximum Series Fuse		**15 A**
Module Efficiency		**19.98 %**
Application Class		**A**
Safety Class		**II**
Cell Type		**Monocrystalline**


RS CORPORATION
'Gayatri' Ganesh Nagar, Near Pethenagar Road, Opposite Lekha Nagar, Nasik-422009
Mo: 7796661999
www.rscorporation.co.in

RS CORPORATION

Jyotitech Solar™
Energising Future

JTS 165 · 165 WP MONOCRYSTALLINE SOLAR MODULE


Module Drawing



Mechanical Parameters

PARAMETER	VALUE
Length of Module	1080 mm ± 1 mm
Width of Module	765 mm ± 1 mm
Height of Module	30 mm ± 0.5 mm
Mounting Hole	10 × 6.4 mm (Oblong), 4 nos.
X-Pitch	735 mm ± 1 mm
Y-Pitch	750 mm ± 1 mm
Grounding Hole	Ø 4 mm
Weight of Module	9.5 kg

All dimensions in millimetres. JB = junction box. Mounting and grounding holes are enlarged in the drawing for clarity.



JTS 165 · Illustrative image

RS CORPORATION
'Gayatri' Ganesh Nagar, Near Pethenagar Road, Opposite Lekha Nagar, Nasik-422009
Mo: 7796661999
www.rscorporation.co.in