RS CORPORATION

Jyotitech Solar™
Energising Future

TECHNICAL DATA SHEET

JTS 300


300 Wp Mono
Solar Module

300 Wp
MAXIMUM POWER

20.6 %
MODULE EFFICIENCY

1500 V DC
MAX. SYSTEM VOLTAGE

Class II
SAFETY CLASS



1285 × 1133 × 30 mm · 15 kg · Illustrative image

Electrical Parameters

PARAMETER	SYMBOL	VALUE
Maximum Power	P_{max}	**300 Wp**
Maximum Power Tolerance		**± 2 %**
Maximum Power Voltage	V_{mp}	**20.82 V**
Maximum Power Current	I_{mp}	**14.41 A**
Open Circuit Voltage	V_{oc}	**24.77 V**
Short Circuit Current	I_{sc}	**15.27 A**
Maximum System Voltage		**1500 V DC**
Maximum Series Fuse		**15 A**
Module Efficiency		**20.6 %**
Application Class		**A**
Safety Class		**II**
Cell Type		**Mono**


RS CORPORATION
'Gayatri' Ganesh Nagar, Near Pethenagar Road, Opposite Lekha Nagar, Nasik-422009
Mo: 7796661999
www.rscorporation.co.in

RS CORPORATION

Jyotitech Solar™
Energising Future

JTS 300 · 300 WP MONO SOLAR MODULE


Module Drawing



Mechanical Parameters

PARAMETER	VALUE
Length of Module	1285 mm ± 1 mm
Width of Module	1133 mm ± 1 mm
Height of Module	30 mm ± 0.5 mm
Mounting Hole	10 × 6.4 mm (Oblong), 4 nos.
X-Pitch	1098 mm ± 1 mm
Y-Pitch	860 mm ± 1 mm
Grounding Hole	Ø 4 mm
Weight of Module	15 kg

All dimensions in millimetres. JB = junction box. Mounting and grounding holes are enlarged in the drawing for clarity.



JTS 300 · Illustrative image

RS CORPORATION
'Gayatri' Ganesh Nagar, Near Pethenagar Road, Opposite Lekha Nagar, Nasik-422009
Mo: 7796661999
www.rscorporation.co.in